

Grass silage spreader JUMBO II

**Three-point attachment frame with support stands,
gear box frame with spreader rollers, safety bow**
for front and rear attachment; working width: 2,25m/2,85m

Type: JJSV-NHS/-NFS 225/285

Price: valid from April 2012

RECK

Agrartechnik

Reck-Technik GmbH & Co. KG
Reckstraße 1-5
88422 Betzenweiler

Telefon +49 73 74 18-82
Telefon +49 73 74 18-13
kontakt@reck-agrartechnik.de
www.reck-agrartechnik.de

pictu nr.	Denomination	Quantity per machine	Identification/ order number	Price [€/pc.] without VAT
Page 1: Three-point attachment frame with support stands				
1	Protective cap PVC for profile shaft 1 3/8"	1	100.000.477	2,60
2	Hexagon nut DIN 936 - M12 - 17H - galvanized	4	100.000.199	0,20
3	Toothed lock washer DIN 6797 - J13 - galvanized	4	100.000.200	0,10
4	PTO guard 8202	1	100.001.995	23,00
5	Washer ISO 7093 - 13 - galvanized	4	100.000.437	0,20
6	Hexagon nut ISO 4032 - M12 - 8 - galvanized	4	100.000.203	0,20
7	Washer ISO 7089 - 13 - galvanized	4	100.000.201	0,10
8	Retaining ring DIN 471 - AS35x2,5	2	100.000.209	2,50
9	Spline shaft 1 3/8"	1	100.001.996	
10	Conical grease nipple DIN 71412 - M6x1 - H1 - galvanized	3 (2)	100.000.196	0,40
11	Flange bearing unit HC 207 d35	1	100.001.744	
12	Bearing distance plate	1	100.001.997	
13	Lower link pin	2	100.000.137	21,00
14	Linch pin 11x55, galvanized	4	100.000.468	2,30
15	Plastic cover cap GL 42x2-4, black	2	100.001.571	0,70
16	Support stay	2	100.001.998	31,50
17	PTO shaft holder	1	100.001.999	
18	Hexagon nut ISO 4032 - M8 - 8 - galvanized	8 (4)	100.000.493	0,10
19	Washer ISO 7089 - 8,4 - galvanized	8 (4)	100.000.454	0,10
20	Hexagon bolt ISO 4017 - M12x30 - 8.8 - galvanized	8 (4)	100.000.382	0,50
21	Washer DIN 7349 - 13 - galvanized	8 (4)	100.000.410	0,30
22	Conical grease nipple DIN 71412 - M6x1 90° - H3 - galvanized	3 (2)	100.001.900	0,20
23	Cylinder pin long	2	100.002.000	
24	Distance bush	8 (4)	100.002.001	
25	Hydraulic cylinder Type JSV ø60xø30x120	2	100.001.774	
26	Spring cotter pin ISO 7072 - ø4, double bent - galvanized	1	100.001.560	0,75
27	Top link pin	1	100.002.002	
28	Three-point attachment frame	1	100.002.003	
29	Swivel pin top	1	100.002.004	
30	Slide bearing bushing	4 (2)	100.001.746	
31	Splint pin ISO 1234 - 5x63 - galvanized	2	100.001.549	0,20
32	Castle nut DIN 935 - M27x1,5 - 8 - galvanized	2	100.001.508	
33	Washer DIN 7349 - 28 - galvanized	2	100.001.532	3,50
34	Swivel pin bottom	1	100.002.005	
35	Hexagon nut ISO 4032 - M6 - 8 - galvanized	18 (12)	100.001.298	0,10
36	Washer ISO 7094 - 6,6 - galvanized	18 (12)	100.001.524	0,10
37	Hexagon bolt ISO 4017 - M6x20 - 8.8 - galvanized	28 (12)	100.001.901	0,10
38	Protection mat	2	100.002.006	
39	Guard plate for protection mat	2	100.002.007	
40	Hexagon bolt ISO 4017 - M8x20 - 8.8 - galvanized	4	100.001.620	0,20
41	Flange bearing unit HC 207 d35	1	100.001.745	
42	Hexagon bolt ISO 4017 - M12x100 - 8.8 - galvanized	4	100.001.465	1,60

Grass silage spreader JUMBO II

**Three-point attachment frame with support stands,
gear box frame with spreader rollers, safety bow**
for front and rear attachment; working width: 2,25m/2,85m

Type: JJSV-NHS/-NFS 225/285

Price: valid from April 2012

RECK

Agrartechnik

Reck-Technik GmbH & Co. KG
Reckstraße 1-5
88422 Betzenweiler

Telefon +49 73 74 18-82
Telefon +49 73 74 18-13
kontakt@reck-agrartechnik.de
www.reck-agrartechnik.de

pictu nr.	Denomination	Quantity per machine	Identification/ order number	Price [€/pc.] without VAT
	page 2: Gear box frame with spreader rollers			
1	Hexagon bolt ISO 4017 - M6x20 - 8.8 - galvanized	28 (16)	100.001.901	0,10
2	Washer ISO 4032 - M6 - 8 - galvanized	18 (6)	100.001.524	0,10
3	Hexagon bolt ISO 4032 - M6 - 8 - galvanized	18 (6)	100.001.298	0,10
4	Cage nut M6 - galvanized	10	100.001.955	0,70
5	Guard plate left	1	100.002.008	
6	Guard plate right	1	100.002.009	
7	Blanking plug POP - 1093, black	2	100.001.749	
8	Conical grease nipple DIN 71412 - M6x1-90° - H3 - galvanized	3 (1)	100.001.900	0,20
9	Slide bearing bushing DIN 1850 - U-shaped - ø50xø60x40x5	4 (2)	100.001.746	
10	Cylinder pin short	2	100.002.010	
11	Washer DIN 7349 - 13 - galvanized	8 (4)	100.000.410	0,30
12	Hexagon bolt ISO 4017 - M12x30 - 8.8 - galvanized	8 (4)	100.000.382	0,50
13	Washer DIN 7089 - 8,4 - galvanized	8 (4)	100.000.454	0,10
14	Hexagon nut ISO 4032 - M8 - 8 - galvanized	8 (4)	100.000.493	0,10
15	Dirt deflector	1	100.002.011	
16	Washer ISO 7089 - 6,4 - galvanized	10	100.000.484	0,10
17	for spreading rollers with working width 2,85m - JJSV 285: Plastic plug PSS 125x130x13,5 natur	2	100.001.990	
18	Punched signet "RECK JUMBO II Grass silage spreader", 572x134,4mm, Traffic blue RAL 5017	2	100.002.058	
19	for spreading rollers with working width 2,25m - JJSV 225: Spreading roller half JUMBO II (1000) left (2,25m working width)	1	100.002.012	1614,00
	for spreading rollers with working width 2,85m - JJSV 285: Spreading roller half JUMBO II (1300) left (2,85m working width)		100.002.014	1742,00
20	for spreading rollers with working width 2,25m - JJSV 225: Spreading roller half JUMBO II (1000) right (2,25m working width)	1	100.002.013	1614,00
	for spreading rollers with working width 2,85m - JJSV 285: Spreading roller half JUMBO II (1300) right (2,85m working width)		100.002.015	1742,00
21	Swivel plate safety bow	1	100.002.016	
22	High strength shackle, A-shaped (curved) with eyebolt	1	100.001.982	
23	Self-locking bolt ISO 8102 - M6x16 - 8.8 galvanized	16	100.001.484	0,20
24	Gear box cover top	2	100.002.017	
25	Klipko® cage nut M6	16	100.001.785	0,90
26	Gear box cover buttom	2	100.002.018	
27	Punced signet "Reck", 400x80mm, Traffic yellow RAL 1023	1	100.002.052	
28	Hexagon bolt ISO 4017 - M10x25 - 8.8 - galvanized	6 (4)	100.001.091	0,50
29	Connection plate	1	100.002.019	
30	Washer ISO 7089 - 10,5 - galvanized	8 (4)	100.000.463	0,10
31	Hexagon nut ISO 4032 - M10 - 8 - galvanized	24 (20)	100.000.229	0,10
32	Sechskantschraube ISO 4017 - M20x60 - 8.8 - verzinkt	8	100.001.477	3,25
33	Schnorr® safety washer ø20, galvanized	8	100.001.755	0,90
34	Clamping sleeve for gear box	8	100.002.024	
35	Gear box frame	1	100.002.020	
36	Washer ISO 7093 - 10,5 - galvanized	36	100.000.517	0,20
37	Hexagon bolt ISO 4017 - M10x30 - 8.8 - galvanized	20 (16)	100.000.475	0,50

Grass silage spreader JUMBO II

**Three-point attachment frame with support stands,
gear box frame with spreader rollers, safety bow**
for front and rear attachment; working width: 2,25m/2,85m

Type: JJSV-NHS/-NFS 225/285

Price: valid from April 2012

RECK

Agrartechnik

Reck-Technik GmbH & Co. KG
Reckstraße 1-5
88422 Betzenweiler

Telefon +49 73 74 18-82
Telefon +49 73 74 18-13
kontakt@reck-agrartechnik.de
www.reck-agrartechnik.de

pictu nr.	Denomination	Quantity per machine	Identification/ order number	Price [€/pc.] without VAT
38	<i>using a cam clutch EK64/12R and EK64/12L:</i> Hexagon bolt ISO 4014 - M10x65 - 8.8 - galvanized	6	100.001.937	0,70
	<i>using a friction clutch EK96:</i> Hexagon bolt ISO 4014 - M10x60 - 8.8 - galvanized	6	100.001.410	0,70
39	Conical grease nipple DIN 71412 - M6x1 - H1 - galvanized	3 (1)	100.000.196	0,40
40	Double joint DG 2400 (FG118TK)	1	100.001.984	
41	<i>using a friction clutch EK96:</i> Distance washer for friction clutch EK96 (depth=3mm)	1	100.002.021	
42	<i>using a cam clutch EK64/12R and EK64/12L:</i> Distance washer for cam clutch EK64 (depth=10mm)	1	100.002.022	
43	Joint mounting	1	100.002.023	
44	<i>using a JJSV-NHS 225/285 (rear linkage):</i> Cam clutch clockwise EK64/12R	1	100.001.985	909,00
	<i>using a JJSV-NFS 225/285 (front linkage):</i> Cam clutch counterclockwise EK64/12R		100.001.986	909,00
	<i>or:</i> Friction clutch EK96	1	100.001.994	
45	Angular spur gearbox	1	100.001.748	
46	<i>using a JJSV-NHS/-NFS 225</i> Cap for hexagon nut SW30, black	1	100.001.991	
47	Hexagon nut ISO 7042 - M20 - 8 - galvanized	2	100.001.308	2,10
48	Cover washer	2	100.002.025	
49	Distance piece SW61 (t=10mm)	2	100.002.026	
50	Hexagon output shaft	1	100.002.028	
	<i>not shown:</i>			
	Adjustable angular fitting, metric 08L, without union nut	4	100.001.778	
	T-fitting TV, metric 08L	2	100.001.779	
	High-pressure line: length: 1,00m	2	100.002.033	
	High-pressure line with plug and dust cap; length: 1,75m	2	100.002.035	
	page 3: Safety bow			
1	Threaded pin ISO 4029 - M8x12 - 45H - galvanized	2	100.001.289	0,20
2	Width adjustment connection pipe	1	100.002.029	
3	Bow left	1	100.002.031	
4	Bow right	1	100.002.032	
5	Hexagon bolt ISO 4017 - M10x25 - 8.8 - galvanized	6 (2)	100.001.091	0,50
6	Adapter safety bow	1	100.002.030	
7	Hexagon bolt ISO 4017 - M10x30 - 8.8 - galvanized	20 (4)	100.000.475	0,50
8	Washer ISO 7093 - 10,5 - galvanized	40 (4)	100.000.517	0,20
9	Washer ISO 7089 - 10,5 - galvanized	8 (4)	100.000.463	0,10
10	Hexagon nut ISO 4032 - M10 - 8 - galvanized	24 (4)	100.000.229	0,10